

```

using System;
using System.Reflection;

namespace sb54_CSAI.ClientApp
{
    #region CliConfigInfo CLASS
    /// <summary>
    /// Holds configuration information that the ReMP3 client application
    /// uses at various different places
    /// </summary>
    public class CliConfigInfo
    {
        #region Instance fields
        ///instance fields
        private static String defaultLocation = "localhost";
        private static String svrLocation=defaultLocation;
        private static String defaultVersion = "1.0.0.0";
        private static String assVersion=defaultVersion;
        #endregion
        #region Public Methods/Properties
        /// <summary>
        /// Gets/Sets the ReMP3 server application address, as a hostname string.
        /// For example JEDI01 or BUDHA01 could be set and returned. TCPIP addresses
        /// will not be accepted or returned.
        /// This is set by the <see cref="sb54_CSAI.ClientApp.FrmClientLoader">ReMP3 client
        loader form </see>
        /// and used by the <see cref="sb54_CSAI.ClientApp.ClientRemoting">ReMP3 client
        remoting class</see></summary>
        public static String svrAdress
        {
            get
            {
                return CliConfigInfo.svrLocation;
            }
            set
            {
                CliConfigInfo.svrLocation = value;
            }
        }

        /// <summary>
        /// Gets/Sets the application version for the ReMP3 application.
        /// This is set by the <see cref="sb54_CSAI.ServerApp.FrmMain">ReMP3 main form </
        see>
        /// and used by the <see cref="sb54_CSAI.ServerApp.FrmAbout">ReMP3 about form</see>
        </summary>
        public static String appVersion
        {
            get
            {
                return CliConfigInfo.assVersion;
            }
            set
            {
                CliConfigInfo.assVersion = value;
            }
        }
        #endregion
    }
}
#endregion

```